

型号含义 Type meaning



10kV级S(B)H15-M系列非晶合金油浸式变压器技术参数 Tech data of 10kV S(B)H15-M series amorphous alloy distribution transformer

额定容量 Rated capacity (kVA)	电压组合(kV) Voltage group	联结方式 Vector group	阻抗电压 (%) Impedance voltage	损耗(kW) Loss		空载电流 (%) No-load current		重量(kg) Weight			外形尺寸(mm) (长×宽×高) Outline dimension	轨距 纵向/横向 Gauge Vertical/ Horizontal
				空载 No-load	负载(75°C) Load	器身重 Body	油重 Oil	总重 Total				
30	高压(HV) 11 10.5 10 6.3 6	Dyn11	4	0.033	0.600	1.7	240	80	410	920X600X980	400X550	
50				0.043	0.870	1.3	310	110	510	950X620X1040	400X550	
63				0.050	1.040	1.2	350	125	570	990X670X1040	400X550	
80				0.060	1.250	1.1	410	135	630	1030X720X1040	400X660	
100				0.075	1.500	1.0	475	150	720	1060X770X1070	400X660	
125				0.085	1.800	0.9	550	170	830	1060X900X1070	400X660	
160				0.100	2.200	0.7	630	190	960	1060X930X1150	400X660	
200				0.120	2.600	0.7	670	210	1040	1110X930X1170	550X820	
250				0.140	3.050	0.7	750	240	1160	1180X1010X1180	550X820	
315				0.170	3.650	0.5	810	265	1240	1180X1010X1180	550X820	
400	低压(LV) 0.4	Dyn11	4	0.200	4.300	0.5	860	290	1330	1200X1010X1180	550X820	
500				0.240	5.150	0.5	950	320	1460	1270X1160X1200	660X1070	
630				0.320	6.200	0.3	1120	380	1860	1450X1240X1330	820X1070	
800				0.380	7.500	0.3	1340	410	2230	1520X1380X1460	820X1070	
1000				0.450	10.30	0.3	1620	540	2700	1720X1460X1510	820X1070	
1250				0.530	12.00	0.2	1900	640	3180	1780X1500X1690	820X1070	
1600				0.630	14.50	0.2	2560	680	4240	1880X1540X1970	820X1070	
2000				0.750	17.40	0.2	2900	960	4920	2080X1580X1970	820X1070	
2500	0.900	20.20	0.2	3940	1160	6560	2350X1580X2020	820X1070				

注:高压分接范围:±5%或±2×2.5%;频率:50Hz;绝缘水平:LI 75AC35/LI OACS

Note:tapping range of HV: ±5% or ±2×2.5%; frequency:50Hz; insulating level:LI 75AC35/LI OACS