

## 型号含义 Type meaning



## 产品标准 Product standard

GB 8266-2005    GB 3836-2000  
 GB/T10228-2008    GB1094.11-2007

## 6kV级KBSGZY系列矿用隔爆型移动变电站技术参数 Tech data of 6kV KBSGZY series mining flameproof movable substation

额定容量 Rated capacity (kVA)	电压组合(kV) Voltage group	联结方式 Vector group	阻抗电压(%) Impedance voltage	损耗(kW) Loss		空载电流(%) No-load current	重量(kg) Weight	外形尺寸(mm) (长L×宽B×高H) Outline dimension	轨距(mm) Gauge	
				空载 No-load	负载(145℃) Load					
50	高压(HV) (6±5%) 低压(LV)	Yy0 (d11)	4	0.350	0.550	2.5	2350	3290X950X1160	600	
100				0.520	0.920	2.5	2600	3580X950X1430		
200				0.820	1.550	2	3050	3710X950X1445		
250				0.950	1.800	2	3300	3820X965X1530		
315				1.100	2.150	1.8	3500	3870X975X1540		
400				1.300	2.600	1.8	3600	3890X995X1550	600 900	
500				1.500	3.100	1.5	4100	3910X1050X1570		
630				1.800	3.680	1.5	5360	4085X1080X1450		
800				2.050	4.500	1.0	5680	4085X1080X1510		
1000				2.350	5.400	1.0	6500	4100X1130X1540		
1250	1.2	Yd0(d11) Dyn11	4.5	2.750	6.500	1.0	6700	4190X1160X1610	600 900	
1600	3.45			3.350	8.000	0.8	9230	4190X1200X1750		
2000				3.800	9.500	0.6	9930	4570X1220X1790		
2500				5	4.500	10.600	0.6	13830		4580X1230X1850
3150				5.5	5.300	12.500	0.6	17250		4820X1260X1890
4000				6	6.100	14.000	0.6	19810		4930X1400X1920

## 型号含义 Type meaning



## 10kV级KBSGZY系列矿用隔爆型移动变电站技术参数

### Tech data of 10kV KBSGZY series mining flameproof movable substation

额定容量 Rated capacity (kVA)	电压组别(kv) Voltage group	联结方式 Vector group	阻抗电压(%) Impedance voltage	损耗(kW) Loss		空载电流(%) No-load current	重量(kg) Weight	外形尺寸(mm) (长Lx宽Bx高H) Outline dimension	轨距(mm) Gauge			
				空载 No-load	负载(145℃) Load							
50	高压(HV) (6±5%)	Yy0 (d11)	4	0.390	0.680	2.5	2400	3200X950X1295	600			
100				0.560	1.050	2.5	2800	3580X950X1430				
200				0.950	1.800	2	3200	3990X950X1525				
250				1.100	2.100	2	3500	4020X950X1540				
315				1.300	2.500	1.8	3800	4050X980X1555				
400				1.500	3.000	1.8	4000	4200X1050X1610				
500				低压(LV) 0.693/0.4	Yd0(d11) Dyn11	4.5	1.750	3.500	1.5	4300	4200X1050X1610	600 900
630							2.000	4.100	1.5	5400	4370X1080X1450	
800							2.300	5.100	1.2	5700	4370X1080X1600	
1000							2.600	6.100	1.2	6900	4400X1110X1675	
1250	1.2	3.100	7.400	1.0			7300	4480X1125X1740				
1600	3.45	3.800	8.500	1.0			9300	4640X1245X1830				
2000		5	4.500	9.700			0.7	11900	4665X1250X1900			
2500		5.5	5.200	10.800			0.7	14930	4870X1390X1900			
3150		5.5	6.100	12.800			0.7	19350	4880X1390X1900			
4000		6	7.000	15.000			0.7	21910	5210X1450X1900			